



Kauden Avauskisa 2026 - FYR Kokkola




Oil Pattern Distance	40	Reverse Brush Drop	36	Oil Per Board	45 ul
Forward Oil Total	7.785 mL	Reverse Oil Total	10.53 mL	Volume Oil Total	18.315 mL
Tank Configuration	A Only	Tank A Conditioner	GLIDE	Tank B Conditioner	CURRENT

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	4L	4R	2	14	3	A	66	0.0	1.9	1.9	2970
2	8L	8R	1	18	3	A	25	1.9	4.4	2.5	1125
3	9L	9R	1	22	3	A	23	4.4	7.5	3.1	1035
4	10L	10R	2	26	3	A	42	7.5	14.8	7.3	1890
5	12L	12R	1	26	3	A	17	14.8	18.4	3.6	765
6	2L	2R	0	30	3	A	0	18.4	40.0	21.6	0

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	3	A	0	40.0	33.0	-7.0	0
2	12L	12R	2	18	3	A	34	33.0	27.9	-5.1	1530
3	10L	10R	4	18	3	A	84	27.9	17.7	-10.2	3780
4	6L	6R	4	14	3	A	116	17.7	9.8	-7.9	5220
5	2L	2R	0	14	4	A	0	9.8	3.0	-6.8	0
6	2L	2R	0	10	4	A	0	3.0	0.0	-3.0	0

Cleaner Ratio Main Mix 19:1 Forward
Cleaner Ratio Back End Mix 19:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5.31	1.42	1	1	1.42	5.31

